

AC Clamp Meter : M266C

Specifications	Range	Resolution	Accuracy
DC Voltage	200mV	0.1mV	$\pm(0.5\%+1)$
	2V/20V/200V	1mV/10mV/0.1V	$\pm(0.5\%+3)$
	1000V	1V	$\pm(0.8\%+3)$
AC Voltage	200V	0.1V	$\pm(1.0\%+5)$
	750V	1V	$\pm(1.2\%+5)$
AC Current	20A	10mA	$\pm(4.0\%+5)$
	200A	0.1A	$\pm(2.5\%+5)$
	1000A	1A	$\pm(3.0\%+10)$
Resistance	200 Ω	0.1 Ω	$\pm(1.0\%+5)$
	20k Ω	10 Ω	$\pm(1.0\%+8)$
	2M Ω	1k Ω	$\pm(1.0\%+8)$
Temperature	0°C~400°C (32°F~752°F)	1°C	$\pm(1.0\%+3)$
	401°C~750°C (752°F~1382°F)	1°F	$\pm(2.0\%+3)$
Insulation Test	20M Ω	10k Ω	$\pm(2.0\%+2)$
	2000M Ω (Note<500M Ω)	1M Ω	$\pm(4.0\%+2)$
	2000M Ω (Note>500M Ω)	1M Ω	$\pm(5.0\%+2)$